



Proveeduría y Servicios Industriales S.A.

323U/D and 323U/4D Metering and Transfer Pump

Specifications

Shipping Weight: 9.9lbs

Maximum Power Consumption: 100VA

Supply: 100-120/220-240V 50-60Hz (voltage selectable)

Maximum Rotor Speeds: 400 rpm

Enclosure: IP31 wipedown

Operational Temperature Range: 4°C to 40°C (40°F to 104°F)

Control Range: 133:1

Noise: <70dBA at 1 meter

Standards: Equipment complies with all applicable CE directives

Materials of Construction

Pumphead

Pump Track & Lever: IXEF

Rollers: Nylatron

Spindles: Electroless nickel plated hardened steel

Bearings: Bronze bush

Drive

Drive Base: Powder coated aluminum casting

Drive Top: ABS Plastic

Bayonet Mounting Plate: IXEF

Available Tubing Materials

1.6 mm wall for 313D & 314D

Bioprene®

Marprene®

Silicone



Proveeduría y Servicios Industriales S.A.

Neoprene (excl. 0.5 mm)

Butyl (excl. 0.5&0.8mm)

Tygon® (excl. 0.5&0.8)

Fluorel™ (excl. 0.5&0.8mm)

Sta-Pure™ (excl. 0.5&0.8mm)

Chem-Sure™ (excl. 0.5&0.8mm)

2.4 mm wall for 313D2 & 314D2

Bioprene® (excl. 0.5&0.8mm)

Marprene® (excl. 0.5&0.8mm)

Silicone

Sta-Pure™ (excl. 0.5&0.8mm)

Chem-Sure™ (excl. 0.5&0.8mm)

Una de sus aplicaciones es para film coating.

Distribuidor Autorizado de las bombas Peristálticas Watson Marlow para todo el territorio Ecuatoriano es PROINSERVI S.A. - Guayaquil.