



Proveeduría y Servicios Industriales S.A.

## Válvula seguridad Criogénica Modelo RXSO-S 760

Detalles técnicos

Procedencia Estados Unidos

Special Teflon® seat, making bubble-tight seals possible to over 90% of set pressures per spec API 527; not applicable to steam.

Adjustable blowdown ring

Cleaned and packaged for use in O2 service in compliance with the CGA specification G-4.1

Additional cleaning specifications:

4WPI-SW70003 ES.660.503

GS-38

GS-40

### APPLICATION DATA

Especially recommended where corrosive or expensive gases benefit from stainless steel construction.

Overpressure relief of tanks, pipelines, vessels, pumps

Stationary Cryogenic storage tanks

Dual Safety relief systems

Air and gas compressors

### APPLICABLE CODES

CGA S-1.2 and S-1.3.

V-4301 (Cryogenic Non-Oxygen)

V-4401 (Oxygen)

ASME sec.VIII

API 527

AD-Merkblatt A2

CRN 0G0591.9C

### OPTIONS

Large and Extra Large Capacity

BSP threads are available on most sizes.

Lever operation

Electropolish

Test Reports available

### MODELS

760 Stainless Steel ASME w/O2 cleaning

765 Stainless Steel PED w/O2 cleaning