



Proveeduría y Servicios Industriales S.A.

Modelo D50

DETALLES TECNICOS

Modelo D50

VALVULA REDUCTORA DE PRESION

PRESIONES hasta 300 PSIG y hasta 420°F

Acción Directa

Vapor, Agua y Gas

Spherical Seating Surface on Floating

Stainless Steel Disc for Tight Shutoff

4 Rangos para el Resorte

Filtro integrado de Acero inoxidable

ANSI/FCI 70-2 Class IV Shutoff

OPTIONS

Teflon© Disc for Dead-end Service for Liquid and Gas

APPLICATION DATA

Steam Irons

Autoclaves

Laundry Mangles

Single Radiators

Steam Tables

Vulcanizers

VALVE RATINGS

Pressure Temperature

PSIG (bar) °F (°C)

Body Material

WITH ST. STL. DISC

Cast Iron 200 (13.8) @ 400 (204.4)

Bronze 300 (21.0) @ 430 (215.6)

Stainless Steel 300 (21.0) @ 420 (215.6)

WITH TEFLON© DISC

All 300 (21.0) @ 300 (148.9)

200 (13.8) @ 400 (204.4)

SPRING RANGES

3-15 All Sizes 75-140 1/2 - 11/4"

10-50 1/2-11/4" 30-100 11/2 -2"

25-80 1/2-11/4" 10- 40 11/2 -2"